

## DX Cleaners

DX Cleaners are specifically designed to remove wax, grease, silicones, road tar, engine oil, overspray, adhesives and other contaminants.

DX Cleaners are packaged ready-to-use.



### Products

- DX320 Fast Evaporating Cleaner
- DX330 ACRYLI-CLEAN® Wax & Grease Remover
- DX394 1.4 Low VOC Cleaner
- DX440 DITZ-O® Wax & Grease Remover

**Note:** These products are not recommended for use on plastic or fiberglass.

# DX Cleaners

## DX320:



- DX320 Fast Evaporating Cleaner should be used as a final cleaning wash prior to painting.
- Clean the surface with DX330, DX394, or DX440 as below prior to sanding, taping, priming, and sealing.
- DX320 may be used to remove surface contaminants such as finger prints left after taping.
- DX320 may be used over all OEM finishes, bare metal surfaces, and cured and dried refinish systems. **Do not use DX320 on plastic or fiberglass.**
- After final taping and prior to sealer or paint application, apply DX320 liberally to the surface to be cleaned. Wipe immediately with a clean, white cloth.
- Do not allow DX320 to dry on the surface.
- Clean an area no larger than 2' X 2' to avoid premature drying.

## DX330:

## DX394:

## DX440:



- Wash surface with soap and water before cleaning.
- Clean surface before and after sanding.
- Apply a generous amount of DX330, DX394, or DX440 with a clean, white cloth or a hand held spray bottle.
- Initial application floats contaminants to the surface. Wipe with a clean, dry cloth to remove the contaminants.
- For maximum results, wipe dry with clean, white cloth in one direction only, while the surface is still wet, to eliminate smearing of contaminants.

**Do not use DX330 or DX440 on plastic or fiberglass parts.** Application on these surfaces can generate static build-up, which can result in flash fire.

**Do not use DX440 on soluble materials like lacquer primers or topcoats.**

## Technical Data:

	<u>DX320</u>	<u>DX330</u>	<u>DX394</u>	<u>DX440</u>
VOC content : lbs./US Gal:	6.31	6.36	1.32	6.46
VOC content: g/L	756	762	158	774

## See Material Safety Data Sheet and Labels for additional safety information and handling instructions.

**Important:** The contents of this package must be blended with other components before the product can be used. Before opening the packages, be sure you understand the warning messages on the labels of all components since the mixture will have the hazards of all its parts. Improper spray technique may result in a hazardous condition. Follow spray equipment manufacturer's instructions to prevent personal injury or fire. Follow directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

### EMERGENCY MEDICAL OR SPILL CONTROL INFORMATION (412) 434-4515; IN CANADA (514) 645-1320

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the public. Products mentioned may be hazardous and should only be used according to direction, while observing precautions and warning statements listed on label. Statements and methods described are based upon the best information and practices known to PPG Industries. Procedures for applications mentioned are suggestions only and are not to be construed as representations or warranties as to performance, results, or fitness for any intended use, nor does PPG Industries warrant freedom from patent infringement in the use of any formula or process set forth herein.

PPG Automotive Refinish  
19699 Progress Drive  
Strongsville, OH 44149  
800.647.6050

PPG Canada Inc.  
2301 Royal Windsor Drive, Unit #6  
Mississauga, Ontario L5J 1K5  
888.310.4762

Follow us online:



[www.ppgrefinish.com](http://www.ppgrefinish.com)

**PPG Automotive Refinish**  
Bringing innovation to the surface.™

The PPG Logo Bringing innovation to the surface, DELTRON®, Acryli-Clean and Ditz-O are trademarks of PPG Industries Ohio, Inc.

© 2015 PPG Industries, Inc. All rights reserved.

