



# Product Information

## NMP-FREE

SX405

## GRAFFITI REMOVER

### Product Description

SX405 NMP-Free Graffiti Remover is specially formulated to remove graffiti from coated surfaces.

It is easy to apply, has no harsh solvent odour and contains no NMP (N-Methylpyrrolidone).

### Typical uses

Tests have demonstrated that NMP-Free Graffiti Remover removes common materials used for graffiti including spray paint, permanent markers, inks, crayons and lipstick.

When properly used, NMP-Free Graffiti Remover will not damage the coated surfaces, even after repeated cleaning.

Simply apply Graffiti Remover to the surface and wipe with a clean cloth.

Some graffiti materials become more difficult to remove when aged and incomplete removal may result.

Although developed as a Graffiti Remover, internal testing and field trials have also shown the SX405 NMP-FREE GRAFFITI CLEANER to be extremely good at removing some of the “travel wax’s” used, e.g. to protect truck chassis during transport, making it a very versatile product.

### Application Equipment Required

Clean rags, soft natural bristle brush, neoprene or butyl rubber gloves.

Not recommended for use in a pressurised pump sprayer with rubber gaskets.

---

## Application Procedure for Graffiti Remover

*Note: Wear safety goggles and gloves. Avoid prolonged skin contact with Graffiti Remover*

---

### **Application of SX405 NMP-Free Graffiti Remover**

Apply Graffiti remover directly to Graffiti.  
Do not apply to areas larger than 0.5m<sup>2</sup> each time.

### **Contact Time**

Wait approximately 1 minute, keeping area moist with Graffiti Remover, then wipe with clean rags taking care not to spread graffiti.  
If more than two applications of Graffiti Remover are needed to remove stubborn stains, rinse the area with clean water and wipe dry before each additional application.

### **Rinsing and Drying**

Rinse all Graffiti Remover cleaned surfaces with water.  
Masonry walls or aged graffiti may require scrubbing with a soft natural bristle brush.

### **Overcoating**

Allow to dry completely before topcoating. (if required)  
Discard wiping rags in a closed container



### **Health and Safety**

**Please refer to Material Safety Data Sheets for full Health and Safety details.**

- Goggles must be worn when mixing and using to prevent accidental splashing into the eye. If contact occurs with eyes give prolonged irrigation with water and get medical attention immediately.
- Good ventilation and extraction must be provided in the working environment.
- Wear suitable protective equipment to prevent skin contact with this material.
- Do not smoke whilst using this material.
- Do not breathe vapours or overspray. In cases of insufficient ventilation, wear appropriate respiratory equipment.



This product is for professional use only.

The information given in this sheet is for guidance only. Any person using the product without first making further inquiries as to the suitability of the product for the intended purpose does so at his own risk and we can accept no liability for the performance of the product or for any loss or damage (other than death or personal injury resulting from our negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

Drying times quoted are average times at 20°C/68°F. Film thickness, humidity and shop temperature can all affect drying times.



**PPG INDUSTRIES AUSTRALIA  
PTY LIMITED**

**McNaughton Road  
Clayton VIC Australia 3168**

**Tel: 13 2424**

**Fax: 1800 800 819**

**PPG INDUSTRIES NEW ZEALAND  
PTY LIMITED**

**5 Vestey Drive Mt. Wellington  
Auckland New Zealand**

**Tel: 0800 320 320**