

## DESCRIPTION

Johnstone's Trade Wood Primer is solvent based. It can be used internally and externally on new or bare wood surfaces, including softwood, hardwood, plywood, chipboard. It provides the ideal surface for overcoating with Johnstone's Trade Professional Undercoat.

## RECOMMENDED USES



Suitable for interior and exterior use.

## TYPE OF SUBSTRATE

Softwood and non-oily hardwood.

## COLOUR RANGE

White.

## FINISH

N/A.

## VOLUME SOLID

48%

## COVERAGE



Johnstone's Trade Wood Primer will cover approximately 12 square metres per litre depending on the nature and porosity of the surface being painted.

## FILM THICKNESS

Wet: 85µm, dry: 41µm.

## DRYING TIME



Recoatable after 16-24 hours under normal conditions.

## TRANSPORTATION &amp; STORAGE

## STORE AWAY FROM HEAT AND FLAME.

To avoid the risk of spillage, always store and transport in a secure upright position.

## CLEANER

Cleaner: White spirit.

## VOC CONTENT

EU limit value for this product (Cat A/d): 300g/l (2010). This product contains max 300g/l VOC.



## KEY PROPERTIES

- For new and bare timber
- Primer for undercoating

## PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Rub down bare timber surfaces with abrasive paper to remove raised grains and sharp edges. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Apply Johnstone's Trade Woodworks Knotting Solution to knots and resinous areas and allow to dry thoroughly. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com).

## APPLICATION



Ensure maximum ventilation during application and drying. Not recommended for interior use on large surface areas, or in confined spaces. Stir thoroughly before use. Apply liberally brushing firmly into the surface and laying off in the line of the grain. Take care to treat all accessible timber, particularly the end grain. Allow to dry thoroughly before applying the relevant undercoat and finishing paint.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : [www.johnstonestrade.com](http://www.johnstonestrade.com) or call 01924 354354

## SIZES

1 Litre, 2.5 Litre, 5 Litre.