

Technical Data Sheet

HIGH BUILD PRIMER

Product Code:	BHBPAG/B/DG/W
Revision Date:	September 2021
Revision Number:	2

Company:	PPG Industries (UK) Limited
Address:	Needham Road, Stowmarket, Suffolk IP14 2AD U.K.
Telephone:	0044 (0) 1449 773338
Email:	enquiries@ppg.com

Product Description

High Build Primers are a primer-surfacer combining ultra-high filling properties with very quick drying times. Resulting in an easily sanded non-pours surface that is suitable for any topcoat.

Product Features

- Super high build primer fillers
- Available in Beige, Grey, Dark Grey and White
- Fast drying
- Excellent smooth finish
- Very easily sanded
- Supplied with 2 nozzles

Usage

Bodyline aerosols are the ultimate method for the refinishing of small vehicle repairs. They provide economical use of production time and manpower. Ensure appropriate PPE is used and apply in a well ventilated area.

Surface Preparation

The surface must be free from all contamination including rust, grease and moisture. Before use, carefully read and note the warning text on the label.

Application



Before use, shake the aerosol for 2 minutes, after agitator ball is free and spray a sample area. The drying time depends on ambient temperature, humidity of air and thickness of coating applied.



Apply in cross coats at a distance of 250mm from object.



After use turn aerosol upside down, press the nozzle for approx. 5 seconds, and clear valve.

Product Properties



Drying time is 10-25 Minutes



Infrared compatible



Sandable with P400-P500



After use turn aerosol upside down and empty valve

FOR PROFESSIONAL USE ONLY

This data sheet is compiled to be of assistance but without guarantee. Users are responsible for safe working practices. Final determination of suitability of any material is the sole responsibility of the user.