

Agricultural Oxide

DESCRIPTION

Johnstone's Trade Agricultural Oxide is a solvent borne, protective finish formulated for interior and exterior use. It provides a gloss finish that combines excellent opacity with good weather resistance, making it particularly suitable for the long term protection of metal agricultural buildings and structural steel.

RECOMMENDED USES



General usage on metal substrates and metal agricultural buildings and structural steel.

SPECIAL PROPERTIES

Excellent covering power. Good weather resistance.

COLOUR RANGE

Red; Green; Grey; Black.

FINISH

VOLUME SOLID

Gloss

61%.

COVERAGE



Johnstone's Trade Agricultural Oxide will cover approximately 14-16 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME



Recoatable after 16-24 hours under normal conditions.

FILM THICKNESS

Wet: 60μm, dry: 37μm.

TRANSPORTATION & STORAGE

Keep container tightly closed. To avoid the risk of spillage, always store and transport in a secure upright position. STORE AWAY FROM HEAT AND FLAME.

THINNER

Cleaner: White Spirit.

VOC CONTENT

EU limit value for this product (Cat A/d): 300g/l (2010). This product contains max 300g/l VOC.



KEY PROPERTIES

- . Long term protection of metal & steel
- Excellent covering power
- Good weather resistance

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. When painting iron and steel remove all millscale and rust. Prime bare surfaces with the appropriate Johnstone's Trade Specialist Primer. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure maximum ventilation during application and drying. Not recommended for interior use on large surface areas, or in confined spaces. Stir well before use. Easy to apply by brush or roller.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/ transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZE

5 Litre.

