



Consumer Business Group

Construction & Home Improvement Markets

Product Information Sheet

3M™ 2072 Masking Tape



General description

3M™ Masking Tape 2072 is a low adhesion tape, ideal for smooth delicate surfaces. Thanks to its very thin backing a perfect line between protected surface and painted surface can be obtained. It can be removed without any residue within 14 days indoor. The tape is UV resistant.

Product Characteristic	Typical Value*	Test method
Backing	Washi paper	-
Adhesive	Acrylic adhesive	-
Standard roll length	50 m	-
Color	Pink	-
Total thickness	75 µm	AFERA 5006
Adhesion to Steel	0.4 N/cm	AFERA 5001
Tensile Strength	30 N/cm	AFERA 5004
Elongation at break	4 %	AFERA 5004

*These are average values. 3M does not guarantee every product will have these specific test values. Actual values may vary and may be greater than or less than the averages listed.

Applications

For smooth delicate surfaces.

Do not use on rough surfaces.

In case of doubt, test on a small invisible area before use.

Storage

To obtain best performances, store this product under normal conditions of 21°C and 50% relative humidity in the original packaging and use it within one year from date of purchase.

Feature (has)	Advantage (which means)	Benefit (so that)
Acrylic adhesive	Good instant adhesion	Stick easily to the surface
	Minimum adhesion build-up over time	Will remove cleanly
	UV resistance	
Washi paper	Straight line	Easy handling
Backing saturant	Solvent and moisture resistant	Resists paint bleed-through. Helps reduce rework

3M is a trademark of 3M Company.

This product is intended, labeled and packaged for sale to trained and experienced professional users. Unless specifically stated otherwise on the applicable product packaging or literature, this product is not intended, labeled, or packaged for sale to or use by consumers.

IMPORTANT NOTICE: All statements, technical information and recommendations herein are based on tests and studies 3M believes to be reliable. 3M does not warrant or guarantee the accuracy or completeness of this information. Because there are many factors that can affect the use and performance of this product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates this product to determine whether it is fit for a particular purpose, is suitable for the user's method of application, and meets the user's performance specifications and expectations. Before any use, it is always recommended to read and follow the instructions for use and to conduct tests to validate the adequacy of the product with regard to the envisaged use. Any action or use of the product made in breach of these indications is at the risks of the user and consequently 3M cannot be held responsible for whatever negative consequences may arise out of or in connection with any breach of the given instructions and indications. Compliance with 3M instructions for use and other recommendations does not exempt the user from respecting other local applicable rules (safety rules, standards and procedures) governing the use of the concerned product in specific contexts and/or through specific means or tools.

Limitation of Liability: 3M's only obligation shall be to replace such quantity of this 3M product proved to be defective or to return the purchase price. Statements or recommendations not contained herein shall not have any force or effect unless included in an agreement signed by a 3M officer.

3M reserves the right to amend the whole or part of this document at any time, without notice.

Terms and Conditions of product warranty are set forth in contractual documents of sale and subject to mandatory applicable laws.