

GORI 99 EXTREME

Opaque Wood Finish



GORI 99 Extreme Opaque Wood Finish is water repellent, UV-resisting and extremely opaque. Ideal for colour changes - even from dark to light colours. This product offers up to *15 years' durability and optimum protection against mould and fungi on the surface thanks to innovative Slow Release technology. The technology ensures that the active agents, which protect the surface film, are only released when necessary - e.g. in humid conditions. When the climate is dry, the active agents will remain dormant in the product. Therefore, the Slow Release technology gives intelligent protection to the film - when the weather demands it.



KEY PROPERTIES

- ▶ **For windows, doors and cladding**
- ▶ **With Slow Release technology for longer protection**
- ▶ **Quick dry, robust and durable weather resisting protection for new and old wood**

PREPARATION

Rinse with clean water. If the wood is very dirty, you can clean it with a high-pressure cleaner with moderate pressure. Loose fibres and old layers of paint must be removed and decayed wood must be replaced. The surface must be clean, dry and solid before further treatment. The moisture in the wood must not exceed 15+3% at the time of treatment. During application and drying of the final top coat the temperature must be above 5°C and the humidity below 80%. Do not apply wood protection in direct sunlight or at temperatures above 25°C. Special precautions should be taken during surface preparation or pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For more information on our products and service please call 01924 354354.

APPLICATION

Ensure good ventilation during application and drying.

Do not thin. Stir lightly before use. If using more than 1 can of the same colour, intermix before use. Treat fungal or algal growth with a Sterilisation Wash as directed. Treat bare timber surfaces with GORI 11 Wood Preservative* as directed.

Apply 3 x GORI 99 Extreme Opaque Wood Finish along the wood grain for optimum protection and apply 2 maintenance coats and when needed.

*GORI 11 Wood Preservative is not available in ROI.

COVERAGE

Rough wood: 6-8m²/l. Planed wood: 8-10m²/l. depending on the substrate. Do not apply wood protection in direct sunlight.

DRYING TIME

Touch dry: Approximately 1 hour, recoatable after 4hours.

CLEANER

Clean Water

COLOUR RANGE

Available in a tintable colour range. Also available in White.

SIZE

Available in 0.75L, 2.5L & 5L

AFTER USE

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use in soapy water and rinse thoroughly. Do not empty product into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

STORAGE

PROTECT FROM FROST

To avoid the risk of spillage, always store and transport in a secure upright position. Lift with care.

EU limit value for this product (Cat A/e): 130g/l (2010).

This product contains max 50g/l VOC.

SAFE USE INFORMATION

Keep out of reach of children.

Avoid contact with skin and eyes.

Do not ingest.

Do not breathe spray. Wear respiratory protection.

If medical advice is needed have container or label to hand.

Please refer to Product label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency.

SDS available by calling 01924 354 354.

*Up to 15 years' durability is based on correct treatment, construction and condition of the substrate and impact of the weather. Applicable if the application/coverage has been carried out according to the recommendations on this label.

