

## Technical Data

## **High Gloss**

A top quality, high gloss finish, suitable for use over most types of interior and exterior surfaces. The outstanding flow and levelling properties ensure easy brushing together with excellent opacity.

#### Recommended uses

Interior 🗸

Exterior /

### Type of substrate

Wood and metal.

## **Colour availability**

Brilliant White and a range of ready mixed colours (5ltr, 2.5ltr & 750ml) Thousands of tinted colours also available (5ltr, 2.5ltr, 1ltr, 750lml & 500ml)

#### **Finish**

**High Gloss** 

#### Volume solid

60%

#### Coverage

1 litre will cover approximately 12 square metres depending on the nature and porosity of the surface.

## **Drying time**

Recoatable after 16-24 hours.

# Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

#### Film thickness

Wet: 60µm Dry: 36µm

## **Preparation**

Ensure surface to be painted is sound, clean, dry and free from grease. Remove all loose and defective paint. Prime all new and bare surfaces with the appropriate Leyland Primer followed by Leyland Undercoat. Rub down sound previously painted surfaces with fine waterproof abrasive paper to provide a key. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory.

## **Application**

Stir well before use. Suitable for application by brush or roller. The brush should be fully loaded for best results. Apply one or more coats as required and allow 16-24 hours drying between coats under normal conditions. Do not apply over polystyrene surfaces.

## Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses. Replace lid firmly.

#### Warning

- Keep out of reach of children.
- Avoid contact with skin and eyes.
- Do not ingest.
- If medical advice is needed have container or label to hand.
- Please refer to Product Label & Safety
  Data Sheet (SDS) for hazard warnings and
  information on safe handling/use/transport/
  storage/disposal/emergency.
- SDS available: www.leylandtrade.com or call 01924 354354