

## Technical Data Sheet

### PREMIUM SPRAY PAINTS - PRIMERS

Product Code:	PREMIUM SPRAY PAINTS – PRIMERS BPSP_
Revision Date:	September 2021
Revision Number:	2
Company:	PPG Industries (UK) Limited
Address:	Needham Road, Stowmarket, Suffolk IP14 2AD U.K.
Telephone:	0044 (0) 1449 773338
Email:	<a href="mailto:enquiries@ppg.com">enquiries@ppg.com</a>

#### Product Description

Premium Spray primers are high build fast drying acrylic primer fillers. They are suitable for steel, light alloys and some plastics.

#### Product Features

- Excellent corrosion prevention
- Optimizes the gloss finish of the topcoat
- Fast drying with good spraying properties and good coverage
- Excellent adhesion of subsequent topcoat
- Excellent filling properties and easy to sand
- Will adhere to wood, metal, aluminium and many other substrates

#### Usage

Bodyline aerosols are the ultimate method for the refinishing of small vehicle repairs. They provide economical use of production time and manpower.

#### Surface Preparation

De-rust, abrade and clean surfaces prior to coating. The surface must be free from all contamination including rust, grease and moisture. Before use, carefully read and note the warning text on the label.

#### Application



Before use, shake the aerosol for 2 minutes and spray a sample area. The drying time depends on ambient temperature, humidity of air and thickness of coating applied.



Apply in cross coats at a distance of 250mm from object.



After use turn aerosol upside down, press the nozzle for approx. 5 seconds, and clear valve.

## Product Properties



Dust free: 5-10 minutes  
Touch dry: 10-20 minutes



Overcoatable after 2 hours



Sandable after 2 hours

The information contained in this sheet represents our current data and best opinion as to the proper use in handling of this product under normal conditions. Any other use or process is the responsibility of the user.

## FOR PROFESSIONAL USE ONLY

This data sheet is compiled to be of assistance but without guarantee. Users are responsible for safe working practices. Final determination of suitability of any material is the sole responsibility of the user.