

Contract Silk

Leyland Contract Silk is specially formulated to provide a full bodied, high opacity, washable, silk finish to all interior walls and ceilings making it ideal for contract work.

Recommended uses

Interior 🖌 Exterior 🗶

Type of substrate

Plaster and embossed wallcoverings. Also suitable for use on wallboards, concrete, brickwork and blockwork.

Colour availability

Brilliant White and Magnolia (15ltr & 10ltr)

Finish

Silk

Volume solid

27%

Coverage

Leyland Contract Silk will cover approximately 12 square metres per litre depending on the nature and porosity of the surface. When using more than one tin of a colour in the same room, intermix before use.

Drying time

Recoatable after 3-4 hours.

Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position. Protect from frost.

Film thickness

Wet: 90µm Dry: 24µm

Preparation

All surfaces to be painted should be clean, dry and free from loose and flaking material. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Seal absorbent surfaces with a solution of up to 1 part water to 9 parts Leyland Contract Silk.

Technical

Application

Stir well before use. Do not thin, except for absorbent surfaces, or when applying by roller or spray when a small quantity of clean water may be added. Suitable for application by brush, roller or spray. Apply paint evenly by brush or roller and avoid overspreading. If required, a second coat may be applied after 3 to 4 hours. Do not apply in temperatures below 10°C.

Cleaning

Remove as much product as possible from application equipment before washing. Replace lid firmly. Wash equipment immediately after use with warm soapy water. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

Warning

- Keep out of reach of children.
- Avoid contact with skin and eyes.
- Do not ingest.
- Do not breathe spray.
 Wear respiratory protection.
- If medical advice is needed have container or label to hand.
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/ storage/disposal/emergency.
- SDS available: www.leylandtrade.com or call 01924 354354

Contact Technical Advisory for information on +44 (0)1924 354354

www.leylandtrade.com