






Technical Datasheet QA-1910_V

 QUICKLINE® Matt Black



Description	<i>Quickline Matt Black, QA-1910</i> , is a conveniently packaged acrylic paint, ideal for touch up repairs and general use.	
Products	QA-1910 <i>Quickline</i> Matt Black	
Surface Preparation	This product should only be applied over well flatted and cleaned substrates in sound condition. Note: This product should not be applied directly over etch primers.	
Mixing 	Supplied Ready for use. Shake aerosol for at least 1 minute before use.	
Application 	Spraying Distance: 15 – 25cm	
Coats 	Apply the finish in several thin layers until a smooth and opaque film is obtained.	
Flash Time 	2 – 3 minutes between coats at 20°C	
Drying 	Air Dry at 20°C	Dust Free: 30 mins Handleable: 60 mins Into Service: 24 hours
VOC Information		
The EU limit value for this product (product category: IIB.e) in ready to use form is max. 840g/litre of VOC. The VOC content of this product in ready to use form is max. 840g/litre. Depending on the chosen mode of use, the actual ready to use VOC of this product may be lower than that specified by the EU Directive code.		

These products are for professional painting only, and are not to be used for purposes other than those specified. The information on this TDS is based on present scientific and technical knowledge, and it is the responsibility of the user to take all necessary steps in order to ensure the suitability of the product for the intended purpose.

Quickline is a registered trademark of PPG Industries Ohio, Inc.
© 2018 PPG Industries, all rights reserved.

Aug 2018

PPG Industries (UK) Ltd
Auto Refinish
Customer Service & Sales Group,
Needham Road
Stowmarket, Suffolk.
IP14 2AD
Tel: 01449 771775

QUICKLINE®