

Wax and Grease Remover

SXA330

ONECHOICE® SXA330 Wax and Grease Remover is specifically designed to remove wax, grease, silicone, road tar, engine oil, overspray, adhesives, and other contaminants. It is an effective cleaner on bare metal substrates, unsanded and sanded undercoats and automotive topcoats.

SXA330 is packaged as an aerosol and is ready for use.



Features & Benefits

- Packaged ready for use
- Produces consistent results
- Lower finishing costs
- Customer satisfaction
- Less waiting
- Increased productivity

Compatible Surfaces

- OEM Surfaces
- Cured and Dried Automotive Surfaces
- Ferrous and Non-Ferrous Metals

Compatible Products

- SXA330 Wax and Grease Remover is for use with all PPG and NEXA AUTOCOLOR® brand products.

Directions For Use

Application:



- Wash surface with soap and water before cleaning with SXA330.
- SXA330 is packaged ready for use.
- For best results use SXA330 before and after sanding.
- Apply a generous amount of SXA330 to a clean dry cloth or directly to the surface. Wipe dry with a clean cloth to remove surface contaminants. A second clean cloth may be needed to completely wipe the surface dry and remove any remaining contaminants.
- For maximum results, wipe dry with clean cloth while the surface is still wet to eliminate smearing of contaminants.
- Do not use SXA330 on plastic or fiberglass parts. Application on these surfaces can generate static build-up which could result in a flash fire.

Can disposal:



When the material in the aerosol can is spent, turn can upside down and depress the nozzle until all propellant is exhausted. Place empty can or cans that are no longer to be used into properly labeled metal containers. The waste containers should be managed as a hazardous waste pursuant to local, state and federal regulations.

Technical Data:

Properties:

RTS Combinations:

SXA330

Volume Ratio	As is
Intended Use	Wax and Grease Remover
VOC Actual (g/L)	691
VOC Actual (lbs./US Gal.)	5.77
Density (g/L)	691
Density (lbs./US Gal.)	5.77

Important:

Before opening the package, be sure you understand the warning messages on the labels of all components, since the mixture will have the hazards of all of its parts. Improper spray technique may result in a hazardous condition. Follow spray equipment manufacturer's instructions to prevent personal injury or fire. Follow directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

See Material Safety Data Sheet and Labels for additional safety information and handling instructions.

EMERGENCY MEDICAL OR SPILL CONTROL INFORMATION (412) 434-4515; IN CANADA (514) 645-1320

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the public. Products mentioned may be hazardous and should only be used according to directions, while observing precautions and warning statements listed on label. Statements and methods described are based upon the best information and practices known to PPG Industries. Procedures for applications mentioned are suggestions only and are not to be construed as representations or warranties as to performance, results, or fitness for any intended use, nor does PPG Industries warrant freedom from patent infringement in the use of any formula or process set forth herein.

PPG Industries

Bringing innovation to the surface.™

PPG Industries
19699 Progress Drive
Strongsville, OH 44149

PPG Canada Inc.
2301 Royal Windsor Drive Unit #6
Mississauga, Ontario Canada L5J 1K5

The PPG Logo, Bringing innovation to the surface, OneChoice., and Nexa Autocolor are trademarks of PPG Industries Ohio, Inc.