

DESCRIPTION

Johnstone's Trade Aqua Guard Satin is our most durable water-based gloss paint for interior wood and metal. Innovative Surface Protection Technology provides the ultimate defence against scratches, wear & tear, and greasy finger marks, for a long-lasting finish. Johnstone's Trade Aqua Guard Satin also has enhanced application qualities with outstanding flow, excellent hiding power and long-lasting whiteness*.

*Long-lasting whiteness is applicable to Brilliant White only.

KEY PROPERTIES

- Ultimate durability
- Resists grease, stains and scratches
- Water-based with outstanding flow and finish

RECOMMENDED USES

INTERIOR

- Suitable for interior use



COLOUR RANGE

Available in a full colour palette via the Johnstone's Tinting System.

FINISH

Satin Finish.

VOLUME SOLID

36%

COVERAGE



Johnstone's Trade Aqua Guard Satin will cover up to 14m²/l depending on the nature and porosity of the surface being painted.

FILM THICKNESS

WET: 100 um DRY: 35 um

DRYING TIME



Touch dry in 2-4 hours
Recoat after 4-6 hours

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. PROTECT FROM FROST

THINNER

Cleaner: Water

VOC CONTENT

EU limit value for this product (Cat A/d): 130g/l (2010). This product contains max 80g/l VOC.



PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Prime bare wood with Johnstone's Aqua Guard Primer Undercoat. Prime all other bare surfaces with Johnstone's Trade Advanced Multi Surface Primer. No primer or undercoat is required on previously painted surfaces, prepare as normal and apply direct; however, for strong colour changes we recommend the Johnstone's Trade Aqua Guard Primer Undercoat in the final colour of choice. Apply one full coat of Johnstone's Aqua Guard Primer Undercoat to all correctly prepared surfaces before application of Johnstone's Trade Aqua Guard Satin. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure good ventilation during application and drying. Stir well. Easy to apply by brush, roller and spray. If more than one can of a colour is to be used in the same area, intermix before use. When attempting a wide colour change additional coats may be required. Do not apply in temperatures below 8°C. When applying by brush, we recommend that you regularly wash the brush out in clean water to prevent drying and clogging of bristles.

SPRAY APPLICATION

HVLP application: 1.8-2.0mm tip size. Spray pressure: 0,3-0,4 MPa (= approx. 3-4 bar). Can be diluted 5-10%. Airless spray application: 0.008" - 0.010" tip, 2000 - 2500psi. Undiluted. Must use Ultra Finish tips.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

1, 2.5 and 5 litre