



DESCRIPTION

Johnstone's Trade Acrylic Durable Matt is a durable, washable matt finish that is suitable for use on interior walls and ceilings. Also, suitable on previously painted or primed wood and metal.

It has Class 1 ISO 11998 scrub rating and is mould resistant, making it an ideal matt finish for internal high traffic areas that can withstand daily wear and tear and repeated washing.

RECOMMENDED USES



Suitable for interior use.

TYPE OF SUBSTRATE

Suitable for interior use on new and previously coated walls & ceilings, as well as new fully dry plaster, dry lining (plaster boards) brick, block, concrete, cement render, suitably primed or previously painted timber and metal, including radiators

COLOUR RANGE

Available in a full colour palette via the Johnstone's Tinting System

FINISH

Matt.

VOLUME SOLID

33,6%

COVERAGE



Johnstone's Trade Acrylic Durable Matt will cover approximately 11-13 square metres per litre depending on the nature and porosity of the surface. If more than one can of a colour is to be used in the same area, intermix before use.

SHEEN LEVEL

5 - 10%

FILM THICKNESS

Wet: 83µm, dry: 28µm.

DRYING TIME



Touch dry in 1-2 hours. Recoatable after 4 hours. Do not apply when air or surface temperature is below 8°C, or in damp conditions

THINNER

Thinner: Clean Water.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. PROTECT FROM FROST

VOC CONTENT



EU limited value for this product (Cat A/a): 30g/l(2010)
This product contains max 0g/VOC

SUSTAINABILITY



KEY PROPERTIES

- Tough, durable & washable.
- Ideal for high wear /traffic areas.
- Resists moisture & Non-yellowing.
- Mould resistant formulation*
- Class 1 Scrub Rating - ISO11998

PRODUCT CREDENTIALS

Class 1 ISO 11998 Scrub Rating

PREPARATION

All surfaces to be painted should be clean, dry and free from grease. Remove any crazed or flaking paint. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during preparation of pre-1960s paint surfaces over wood and metal as they contain harmful lead. For new/bare or absorbent surfaces dilute by up to 20%. Prime bare timber and metal surfaces with an appropriate Johnstone's Trade primer. Allow radiators to cool before painting. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

SYSTEM INFORMATION

- New and bare surfaces – Apply one coat diluted by up to 20%, follow with a minimum of two further coats.
- Absorbent finishes – Apply one coat thinned up to 20%, follow with a further undiluted coat*
- Previous sound coatings – A minimum of two coats*

*Further coats may be required over contrasting colours for full obliteration

APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir well. Easy to apply by brush, roller and spray. If more than one can of a colour is to be used in the same area, intermix before use. Do not apply in temperatures below 8°C or in damp conditions

Seal new and absorbent finishes with an initial coat of Johnstone's Trade Acrylic Durable Matt thinned up to 20% with clean water. Avoid the use of lower performing coatings such as contracts as a base coat. Airless spray recommendations

Tip size: 0.013" - 0.017"
Pressure: 2000 – 2500 PSI

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

*Johnstone's Trade Acrylic Durable Matt contains a biocide to protect paint surface from mould degradation.

SIZES

2,5 Litre, 5 Litre, 10 Litre