





# Alkali Resisting Wall Primer

A solvent-based alkaliresisting primer and sealer for interior and exterior masonry surfaces. Resists alkali attack and promotes first class adhesion. Also suitable for use on other surfaces including wood and fibreglass. Ideal for use under both oilbased and waterborne paints.

#### Recommended uses

Interior

Exterior /

# Type of substrate

Plaster, concrete, cement rendering, brick, stone and blockwork.

# **Colour availability**

White (5ltr & 2.5ltr)

#### **Finish**

N/A

#### Volume solid

57%

#### Coverage

1 litre will cover approximately 10 square metres depending on the nature and porosity of the surface.

## **Drying time**

Touch dry in 4-6 hours. Recoatable after 16-24 hours.

# Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

#### Film thickness

Wet: 50µm Dry: 28µm

# **Preparation**

Ensure surface to be painted is sound, clean, dry and free from grease. Rub down the bare timber surfaces with dry glasspaper to remove raised grain and sharp edges. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Apply Knotting Solution to knots and resinous areas, and allow to dry thoroughly. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory.

## **Application**

Stir well before use. Suitable for application by brush or roller. Apply liberally, working firmly into the surface and laying off in the line of the grain. Take care to treat all accessible timber particularly the end grain. Allow to dry thoroughly before applying the relevant undercoat and finishing paint.

## Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses. Replace lid firmly.

#### Warning

- · Keep out of reach of children.
- · Avoid contact with skin and eyes.
- Do not ingest.
- If medical advice is needed have container or label to hand.
- Please refer to Product Label & Safety
  Data Sheet (SDS) for hazard warnings and
  information on safe handling/use/transport/
  storage/disposal/emergency.
- SDS available: www.leylandtrade.com or call 01924 354354