

DESCRIPTION

Johnstone's Trade Stormshield Silicone Masonry Paint is a high performance masonry coating designed for use over traditional rendered surfaces and existing silicone or prefinished render systems. The technology provides high levels of breathability to allow moisture to leave the surface, resisting damage to the render or paint film. It is extremely durable with 15 years life expectancy and excellent weather resistance. It can be applied from 20C and rising, and is rain resistant after 20 minutes*

RECOMMENDED USES



Ideal for use over masonry, renders, silicone based renders or cementitious surfaces that require a breathable coating.

COLOUR RANGE

Tintable to over 1500 shades including the Johnstones VoC range.

FINISH

Matt

VOLUME SOLID

52%

COVERAGE



Johnstone's Trade Stormshield Silicone Masonry Paint will cover approximately 7-8 square metres per litre depending on the nature and porosity of the surface being painted.

FILM THICKNESS

WFT 130mic , dft 70mic

DRYING TIME



Touch dry in 2 hours. Recoatable after 5 hours under normal, well ventilated conditions. Rain resistant after 20 minutes*

*at 230C and 50% humidity

TRANSPORTATION & STORAGE


To avoid the risk of spillage, always store and transport in a secure upright position. Do not use empty container for storing food. PROTECT FROM FROST.

Cleaner

Cleaner: Clean water.

VOC CONTENT

EU limit value for this product (Cat A/c): 40g/l (2010). This product contains max 5g/l VOC.



KEY PROPERTIES

- Ideal paint for renders
- High levels of water and weather resistance
- Ongoing protection for existing render surfaces
- 15+ years life expectancy

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Repair cracks and defective areas and treat fungal or algal growth with Fungicidal Wash as directed. Stabilise surfaces of a friable nature with Johnstone's Trade Stormshield Quick Dry Stabilising Solution as directed. When applying the first coat direct to new, untreated or porous surfaces, dilute the paint with approximately 5% clean water. Wear a suitable face mask when creating dust.

APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir well. Easy to apply by brush or textured roller. Also suitable for application by airless spray. If more than one can of a colour is to be used in the same area, intermix before use. Do not apply when air or surface temperatures are below 2°C or when rain is imminent.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZE

5ltr