

Heavy Duty Floor Paint – Colours

A hard wearing, protective, satin finish. Based on polyurethane alkyd resins which have been designed to withstand spillage and repeated cleaning. Ideal for use on most concrete and wooden floor areas such as garages, warehouses, workshops and factories, where the application of two coats provide excellent durability.

Recommended uses

Interior ✓ Exterior ✗

Type of substrate

Concrete, and wooden floors. For further advice on other substrates contact Technical Advisory on 01924 354354.

Colour availability

*Clear and a range of ready mixed colours (5ltr & 2.5ltr)

Finish

Mid-sheen

Volume solid

57%

Coverage

1 litre will cover approximately 11 square metres, depending on the nature and porosity of the surface. When using more than one tin of a colour in the same area, intermix before use.

Drying time

Under normal conditions, touch dry in 2-4 hours. Recoatable after 16-24 hours.

Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

Film thickness

Wet: 91µm
Dry: 52µm

Preparation

Ensure all floor surfaces to be painted are sound, clean, dry and completely free from oil, grease and polish. New concrete floors should preferably be allowed to mature for several months before painting and the moisture content should be checked before work commences. Concrete surfaces should also be free of dust, grit, cement fines and laitance. Very dense smooth concrete surfaces (such as power floated concrete) normally require to be acid etched before painting in order to promote satisfactory adhesion.

Application

Stir well before use. Apply two coats, allowing overnight drying between coats under normal drying conditions. Where necessary, to ease application, the first coat may be thinned with up to 5% by volume of White Spirit. Apply by brush or roller.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses. Replace lid firmly.

Warning

- Keep out of reach of children.
- Avoid contact with skin and eyes.
- Do not ingest.
- If medical advice is needed have container or label to hand.
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency.
- SDS available: www.leylandtrade.com or call 01924 354354.

* For Heavy Duty Floor Paint - Clear, please contact Technical Advisory on 1924 354354.