

Technical Data

Wood Primer

Leyland Wood Primer is suitable for use on bare interior and exterior timber surfaces, providing excellent adhesion.

Recommended uses

Interior

Exterior /

Type of substrate

Softwood and non-oily hardwood.

Colour availability

White (5ltr, 2.5ltr & 750ml)

Finish

N/A

Volume solid

48%

Coverage

1 litre will cover approximately 12 square metres depending on the nature and porosity of the surface.

Drying time

Recoatable after 16-24 hours.

Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

Film thickness

Wet: 85µm Dry: 41µm

Preparation

Ensure surface to be painted is sound, clean, dry and free from grease. Rub down the bare timber surfaces with dry glasspaper to remove raised grain and sharp edges. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Apply Knotting Solution to knots and resinous areas, and allow to dry thoroughly. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory.

Application

Stir well before use. Suitable for application by brush or roller. Apply liberally, working firmly into the surface and laying off in the line of the grain. Take care to treat all accessible timber particularly the end grain. Allow to dry thoroughly before applying the relevant undercoat and finishing paint.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses. Replace lid firmly.

Warning

- · Keep out of reach of children.
- · Avoid contact with skin and eyes.
- Do not ingest.
- If medical advice is needed have container or label to hand.
- Please refer to Product Label & Safety
 Data Sheet (SDS) for hazard warnings and
 information on safe handling/use/transport/
 storage/disposal/emergency.
- SDS available: www.leylandtrade.com or call 01924 354354