

## One Coat Gloss

An easy-to-use, self-undercoating gloss paint. Its high opacity means that only one coat is necessary under most conditions. One Coat Gloss dries to a tough, hardwearing gloss finish on both interior and exterior wood and metalwork.

### Recommended uses

Interior ✓ Exterior ✓

### Type of substrate

Wood and metal.

### Colour availability

Brilliant White & Black (2.5ltr & 750ml)

### Finish

High Gloss

### Volume solid

62%

### Coverage

1 litre will cover approximately 10 square metres, depending on the nature and porosity of the surface. Strong or contrasting colours may require additional coats. When using more than one tin of a colour in the same room, intermix before use.

### Drying time

Touch dry in 4-6 hours.  
Recoatable after 16-24 hours.

### Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

### Film thickness

Wet: 100µm  
Dry: 62µm

### Preparation

Ensure surface to be painted is sound, clean, dry and free from grease. Remove all loose and defective paint. Prime all new and bare surfaces with the appropriate Leyland primer. Rub down sound previously painted surfaces with fine waterproof abrasive paper to provide a key. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory.

### Application

Do not stir. The brush should be fully loaded for best results. Occasionally, a small amount of liquid may appear in the tin, if this is not used in the first brushful, remove excess. Apply paint evenly by brush and avoid overspreading. Allow to dry overnight before applying a second coat if required. Do not apply over polystyrene surfaces.

### Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses. Replace lid firmly.

### Warning

- Keep out of reach of children.
- Avoid contact with skin and eyes.
- Do not ingest.
- If medical advice is needed have container or label to hand.
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency.
- SDS available: [www.leylandtrade.com](http://www.leylandtrade.com) or call 01924 354354