

# IS-213 Polyurethane Reducer

## TECHNICAL DATA SHEET

### Product Description

IS-213 Polyurethane Reducer, qualified to MIL-T-81772 Type I, can be used to improve spray characteristics and film appearance of polyurethane topcoats. IS-213 is compatible with polyurethane topcoats qualified to MIL-PRF-85285 and other similar material specifications.

### Specifications



IS-213 is qualified to:

- MIL-T-81772 Type I

*Note: PPG Aerospace recommends you check the most recent specification QPLs for updated information.*

#### **Product Compatibility:**

IS-213 is compatible with the following specifications:

- GC130N
- GP110AEF
- MIL-PRF-85285 Type I, II & IV
- MMS-420

### Instructions for Use



#### **Mixing Instructions:**

Add sufficient amount of IS-213 to the admixed material to achieve the desired viscosity only after the initial viscosity of the admixed material has been determined. The amount to be added is limited by local VOC regulations and is not to exceed one pint per mixed gallon. Each fluid ounce of IS-213 adds approximately 26 grams (0.06pounds) of VOC. The addition of IS-213 will reduce volume solids of the mixed paint. Due to this reduction, achievement of the specified dry film thickness may require thicker wet films or multiple applications. End users must confirm proper dry film thickness is achieved by physical measurement.

Addition of IS-213 may extend the pot life of the mixed material by a dilution effect. Do not add IS-213 to the admixed material that is approaching the end of its pot life.

*Note: It is important to condition the paint for 24 hours prior to mixing by placing all materials in the shop or hangar, with ambient temperatures between 13° to 35°C (55° to 95°F). The minimum temperature of the paint components should be 13°C (55°F) prior to mixing.*

## IS-213 Polyurethane Reducer




**Induction Time:**

Not Required



**Viscosity:** (23°C/73°F)

Not Required



**Pot Life:**

Not Required

### Physical Properties (product)



**Color:**

Clear



**Gloss:**

Not Applicable



**VOC (EPA method 24):**

IS-213

889 grams/liter

**Physical Constants:**

Weight/gallon

7.45 pounds/gallon

Vapor Pressure

26 mmHg at 20°C (68°F)



**Flash Point closed cup:**

IS-213

3°C (38°F)

## IS-213 Polyurethane Reducer

**Shelf Life:**

24 months from date of manufacture for PRC-DeSoto Standard

*Note: Shelf life is provided for original, unopened containers*

*Note: The application and performance property values above are typical for the material, but not intended for use in specifications or for acceptance inspection criteria because of variations in testing methods, conditions and configurations.*

### **Storage Recommendations**



Inspect the condition of the container to ensure compliance. The material should be stored at temperatures between 5°C to 35°C (41°F to 95°F) to ensure shelf life.

*Note: When procuring to a qualified material specification, follow those storage instructions.*



# IS-213 Polyurethane Reducer

## Health Precautions

This product is safe to use and apply when recommended precautions are followed. Before using this product, read and understand the Safety Data Sheet (SDS), which provides information on health, physical and environmental hazards, handling precautions and first aid recommendations. An SDS is available on request. Avoid overexposure. Obtain medical care in case of extreme overexposure.

**For industrial use only. Keep away from children.**

**Additional information can be found at: [www.ppgaerospace.com](http://www.ppgaerospace.com)**

**For sales and ordering information call the local PPG office at the numbers listed below:**

### **Asia Pacific**

#### **ASC – Australia**

Tel 61 (3) 9335 1557  
Fax 61 (3) 9335 3490

#### **ASC – Japan**

Tel 81 561 35 5200  
Fax 81 561 35 5201

#### **ASC – South East Asia**

Tel 65 6861 1119  
Fax 65 6861 6162

#### **ASC – Suzhou**

Tel (86-512) 6661 5858  
Fax (86-512) 6661 6868

#### **ASC – Tianjin**

Tel (86-022) 2482 8625  
Fax (86-022) 2482 8600

### **Americas**

1 (818) 362-6711 or 1-800-AEROMIX

### **Europe and Middle East**

#### **ASC – Central Europe**

Tel 49 (40) 742 193 10  
Fax 49 (40) 742 139 69

#### **ASC – Middle East & India**

Tel (971) 4 883 9666  
Fax (971) 4 883 9665

#### **ASC – North Europe**

Tel 44 (0) 1388 770222  
Fax 44 (0) 1388 770288

#### **ASC – South Europe**

Tel 33 (0) 235 53 43 71  
Fax 33 (0) 235 53 54 44

All recommendations, statements, and technical data contained herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty, either expressed or implied. User shall rely on his own information and tests to determine suitability of the product for the intended use and assumes all risks and liability resulting from his use of the product. Seller's and manufacturer's sole responsibility shall be to replace that portion of the product of this manufacturer which proves to be defective. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss, or damage directly or indirectly resulting from use of, or inability to use, the product. Recommendations or statements other than those contained in a written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller.

PPC-DeSoto International, Inc.  
12780 San Fernando Road  
Sylmar, CA 91342  
[www.ppgaerospace.com](http://www.ppgaerospace.com)

Issue Date: 2/17  
Lit: 4480