

DESCRIPTION

Johnstone's Trade Obliterate Matt is a premium quality interior walls and ceilings emulsion with a smooth flat matt finish, which gives unrivalled opacity in one coat. Offering a time saving solution on site where access and time is limited. Perfectly suited for redecoration in high footfall areas requiring durability, such as stairwells in both domestic and commercial spaces.

KEY PROPERTIES

- Covers in one coat
- Class 1 scrub rating
- Saves time on site

RECOMMENDED USES



Internal finish for all types of Interior walls and ceilings, both bare and previously painted, including plaster, plasterboard, concrete, blockwork, brickwork, cement render, primed substrate, dry lining etc.

COLOUR RANGE

Available in Brilliant White and L Base only

FINISH

Flat Matt Finish
(\leq 2 % Sheen Level)

VOLUME SOLID

39.4%

COVERAGE



Johnstone's Trade Obliterate Matt will cover up to 7 square metres per litre depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet: 155 um / Dry: 61 um

DRYING TIME



Touch dry in 2 hours.
Recoatable if required after 6 hours, under normal conditions.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Lift with care. PROTECT FROM FROST.

THINNER

To achieve full opacity, thinning is not recommended.

VOC CONTENT

EU limit value for this product (Cat A/a): 30g/l (2010). This product contains max 1g/l VOC



PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation or pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

Bare/New surface process

In most instances a single coat will be sufficient to achieve full obliteration of the existing surfaces – i.e. plaster, plasterboard, dry lining etc., however if surface defects, damage and isolated repairs are identified these should be repaired prior to overall application of one full coat of Obliterate Matt.

Redecoration/Previously painted process

In most instances a single coat will be sufficient to achieve full obliteration of the existing coating and colour. However, follow normal painting practices if repairs and filling of defects and damaged areas are required. As part of the initial preparation, we would advise to “spot coat” these areas with a coat of Obliterate Matt prior to overall application of one full coat of Obliterate Matt.

For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com

APPLICATION



Ensure good ventilation during application and drying. Stir well. For best results, apply by brush or roller. Also suitable for application by spray. Do not breathe spray. Wear respiratory protection. If more than one of a colour is to be used in the same area intermix before use. A second coat may be required if overpainting a dark or contrasting colour. Do not apply in temperatures below 10°C.

Spray Application:

Airless spray application: undiluted, spray @ 2000-3000 PSI with 0.019"-0.021" tip.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty waste paint into drains or watercourses, including when cleaning painting tools. Do not use empty container for storing food.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZE

10 Litre