

## Vinyl Silk

A high quality, easy-to-clean, silk emulsion, suitable for interior use, where a dirt-resisting coating is required. The low odour, quick drying properties ensure minimum disruption during application.

### Recommended uses

Interior ✓ Exterior ✗

### Type of substrate

Plaster and embossed wallcoverings. Also suitable for use on wallboards, concrete, cement rendering, brickwork and blockwork in internal situations.

### Colour availability

Brilliant White and a range of ready mixed colours (10ltr, 5ltr, 2.5ltr & 1ltr). Thousands of tinted colours also available (5ltr & 2.5ltr)

### Finish

Silk

### Volume solid

31%

### Coverage

1 litre will cover approximately 12 square metres per litre, depending on the nature and porosity of the surface. Strong or contrasting colours may require additional coats. When using more than one tin of a colour in the same room, intermix before use.

### Drying time

Touch dry in 1-2 hours.  
Recoat after 3-4 hours.

### Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position.  
PROTECT FROM FROST.

### Thinner

Clean water.

### Film thickness

Wet: 83µm  
Dry: 30µm

### Preparation

Ensure surface to be painted is sound, clean, dry and free from grease. Remove all loose and defective paint. Prime where required with the appropriate Leyland Primer. Rub down glossy surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Seal absorbent surfaces with a solution of up to 1 part water to 9 parts Vinyl Silk.

### Application

Stir well before use. Do not thin, except for absorbent surfaces or when applying by roller or spray when a small quantity of clean water may be added. Suitable for application by brush, roller or spray. Apply paint evenly by brush or roller and avoid overspreading. If required, apply a second coat after 3-4 hours. Do not apply in temperatures below 10°C.

### Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses. Replace lid firmly.

### Warning

- Keep out of reach of children.
- Avoid contact with skin and eyes.
- Do not ingest.
- Do not breathe spray.  
Wear respiratory protection.
- If medical advice is needed have container or label to hand.
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency.
- SDS available: [www.leylandtrade.com](http://www.leylandtrade.com) or call 01924 354354