

# Heavy Duty Glaze

#### DESCRIPTION

Johnstone's Trade Heavy Duty Glaze is a tough, durable coating for added protection in high traffic areas such as corridors or areas subject to robust cleaning regimes. Suitable for application over most Johnstone's Trade interior decorative coatings.

#### RECOMMENDED USES



For added protection of interior wall surfaces subject to heavy traffic. Especially suitable as a protective coating.

## SPECIAL PROPERTIES

Tough, durable coating.

## **COLOUR RANGE**

Clear

#### FINISH

## VOLUME SOLID

Gloss.

29%.

## COVERAGE



Johnstone's Trade Heavy Duty Glaze will cover approximately 12 square metres per litre depending on the nature and porosity of the surface being painted.

## FILM THICKNESS

Wet: 83µm, dry: 25µm.

#### DRYING TIME



Touch dry in 2 hours. Recoatable after approximately 4 hours.

#### TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. PROTECT FROM FROST.

### THINNER

Thinner: Clean water.

## VOC CONTENT

EU limit value for this product (Cat A/e): 130g/l (2010). This product contains max 80g/l VOC.



#### KEY PROPERTIES

- Suitable over most Johnstone's Trade finishes
- Highly durable protection from cleaning and knocks

#### PREPARATION

All surfaces to be painted should be sound, clean, dry and free from grease. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com

#### APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear Respiratory Protection. Stir well before use. Suitable for application by brush, spray or mohair roller. Apply a single coat of uniform thickness, taking care to avoid runs or overlapping. Do not apply when air or surface temperature is below 10°C, or in humid conditions.

#### CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use in warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/ transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

## SIZE

5 Litre

