

DESCRIPTION

Johnstone's Trade Stop-Mould is a water borne matt emulsion paint specially formulated to resist mould growth on the paint film in areas susceptible to intermittent damp conditions. Suitable for interior use on new and aged plaster, wallboards, concrete, cement rendering, blockwork and brickwork.

RECOMMENDED USES



Suitable for interior use on new and aged plaster, wallboards, concrete, cement rendering, blockwork and brickwork. For use only in accordance with the directions on the tin.

SPECIAL PROPERTIES

Anti-fungal (mould) film protection.

COLOUR RANGE

Brilliant White; Magnolia.

FINISH

Matt.

VOLUME SOLID

23%

COVERAGE



Johnstone's Trade Stop-Mould will cover approximately 9-11 square metres, depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet: 100µm, dry: 25µm.

DRYING TIME



Touch dry in 1-2 hours. Recoatable after 2-4 hours.

TRANSPORTATION & STORAGE


To avoid the risk of spillage, always store and transport in a secure upright position. PROTECT FROM FROST.

THINNER

Thinner: Clean water.

VOC CONTENT

EU limit value for this product (Cat A/i): 140g/l (2010). This product contains max 5g/l VOC.



KEY PROPERTIES

- For areas prone to damp conditions
- Resists mould growth*
- For interior use

PREPARATION

Ensure the surface to be painted is clean, dry and free from grease and loose or flaking matter. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Wear a suitable face mask when dry sanding. Surfaces already contaminated with mould growth should be treated with Johnstone's Trade Sterilisation Wash as directed. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



To avoid risks to man and the environment, comply with the instructions for use. USE ONLY AS DESCRIBED ON THE LABEL Ensure good ventilation during application and use. Do not breathe spray. Wear Respiratory Protection. Stir well before use. Suitable for application by brush, roller or spray. Seal absorbent surfaces with a coat of Johnstone's Trade Stop-Mould thinned with up to 10% clean water. Do not apply when air or surface temperature is below 8°C.

CLEANING



Remove as much product as possible from application equipment after use. Replace lid firmly. Clean equipment immediately after use with warm, soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses. Do not use empty container for storing food.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZE

5 Litre.

*This paint contains a biocidal product for the preservation of the dry film. Contains: IPBC Contains Biocidal Products: BIT,MIT