
Pot Life



Pot Life:	1 : 1 : 1	Standard:	Indefinite
	1 : 1	Wet Bed:	Indefinite
	1 : 1 +5%	High Temp:	8 hours at 70°F (21°C)

Air Pressure and Gun Setup



HVLP:	8 - 10 psi at the air cap
Compliant:	29 - 40 psi at the gun
Gun Setup:	1.3 - 1.6 mm or equivalent

Note: For best overall results, refer to spraygun manufacturer's recommendations for inlet air pressures.

Application



Coats:	1 - 2 coats or until blend is achieved
	See JBX or JBPX product bulletins for additional information.

Dry Times



Between Coats:	5 - 10 minutes at 70°F (21°C)
-----------------------	-------------------------------



Air Dry:	Dry:	30 minutes minimum, 24 hours maximum at 70°F (21°C) to clearcoat.
	Tape:	45 minutes

***Note:** J105 must be clearcoated

Clean Up

Clean spray guns, gun cups, storage pots, etc., thoroughly with JR Reducer, JT501 General Purpose Solvent or another appropriate clean up solvent after each use.

Follow EPA guidelines for proper storage and disposal of solvent-borne waste paint.

Properties

RTS Combinations:	J105 : JR55X : JBX/JBPX	J105 : JR55X	J105 :JR557 : JH6028
Volume Ratio:	1 : 1 : 1	1 : 1	1 : 1 : 5%
Applicable Use Category	Uniform Finish Ctg.	Uniform Finish Ctg.	Uniform Finish Ctg.
VOC Actual (g/L)	102-103	60	59
VOC Actual (lbs/gal)	0.85-0.86	0.50	0.49
VOC Regulatory (less water less exempt) (g/L)	330-401	312-325	265
VOC Regulatory (less water less exempt) (lbs/gal)	2.75-3.35	2.60-2.71	2.21
Density (g/L)	1132-1228	1252-1255	1247
Density (lbs/gal)	9.45-10.25	10.45-10.47	10.41
Volatiles wt. %	77.2-86.4	89.2-89.7	86.1
Solids by weight %	13.7-22.8	10.3-10.8	13.9
Solids by volume %	13.6-18.9	11.4-12.2	15.4
Water wt. %	0.0	0.0	0.0
Exempt wt. %	68.8-77.2	84.4-85.0	81.4
Water vol. %	0.0	0.0	0.0
Exempt vol. %	69.0-74.2	80.9-81.7	72.7
Sq. Ft. Coverage / US Gal 1 mil at 100% transfer efficiency	218-303	183-196	223



Limitations

Shop-Line products should not be combined with components of other product lines.

Precautionary Information:

The contents of this package may have to be blended with other components before the product can be used. Before opening the packages be sure you understand the warning messages on the labels of all components since the mixture will have the hazards of all of its parts. Spray equipment must be handled with due care and in accordance with manufacturer's recommendations. Follow label directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

Medical Response:

EMERGENCY MEDICAL OR SPILL CONTROL INFORMATION (412) 434-4515; IN CANADA (514)-645-1320

See Safety Data Sheet and Labels for additional safety information and handling instructions.

Data Safety Sheets for the PPG products mentioned in this publication are available through your PPG *Shop-Line* brand distributor. To the best of our knowledge, the technical information in this bulletin is accurate; however, since PPG Industries is constantly improving its coating and paint formulas, the current technical data may vary somewhat from what was available when this bulletin was printed. Contact your *Shop-Line* brand distributor or visit www.ppgrefinish.com for the most up-to-date information.

The PPG Logo, *Shop-Line*, *Multi-Prep*, and *H₂O-So-Clean* are trademarks of PPG Industries Ohio, Inc.