

STEELGUARD™ 951

DECLARATION OF PERFORMANCE No. DOP 951/0

1. Unique identification code of the product-type:	STEELGUARD™ 951
2. Intended use:	Two pack epoxy reactive coating for protection of load bearing steel elements
3. Manufacturer:	PPG Coatings Europe BV, Oceanenweg 2, 1047BB, Amsterdam, The Netherlands
4. Authorised Representative:	Not Applicable
5. System/s of AVCP:	System 1
6a. Harmonised Standard:	Not Applicable
Notified Body/ies:	
6b. European Assessment Document:	
European Technical Assessment:	ETA 22/0790
Technical Assessment Body:	Element Materials Technology Rotterdam B.V.
Notified Body/ies:	Element Materials Technology Rotterdam B.V. NB 2812



STEELGUARD™ 951

DECLARATION OF PERFORMANCE No. DOP 951/0

7. Declared Performance/s:	Essential Characteristics	Performance	Technical Specifications
Basic requirement for construction work: Safety in case of fire			
Fire resistance	I/H section beams and columns R15, R20, R30, R45, R60, R90, R120, R150, R180 – All including slow heating Circular and rectangle/square hollow section columns R15, R20, R30, R45, R60, R90, R120.		EN 13381-8: 2013 EN 13501-2: 2016
Basic requirement for construction work: Hygiene, health and environment			
Release of dangerous substances		The product specification has been compared with the dangerous substances listed on the database established on the EC construction website with the list of regulated dangerous substances possible associated with construction products with Annex XVII and Annex XVI of REACH and with the ECHA candidate list of substances of very high concern to verify that the products does not contain such substances at greater than the tolerated maximum concentration values	EAD 350402-00-1106, September 2017
Basic requirement for construction work: Safety and accessibility in use			
Durability and serviceability; Behavior under different environmental conditions		- Primer and topcoat compatibility Passed exposure conditions: - Type X Durability - Type Y Durability - Type Z ₂ Durability - Type Z ₁ Durability	EAD 350402-00-1106, September 2017
8. Appropriate Technical Documentation and/ or Specific Technical Documentation:	EAD 350402-00-1106, September 2017		



STEELGUARD™ 951

DECLARATION OF PERFORMANCE No. DOP 951/0

STEELGUARD™ 951 – Approved EAD 350402-00-1106 Systems		
Generic Primer Type	DFT Min	DFT Max
Two Component Epoxy	53µm	159µm

Please refer to PPG Information sheet 1224 for the current list of approved primers

Topcoat	DFT Tested	DFT Min	DFT Max	Environmental Conditions			
				Z ₂	Z ₁	Y	X
No Topcoat	-	-	-	✓	✓	✓	✓
SIGMADUR 550 / FREITANE 550	50µm	50µm	75µm	✓	✓	✓	✓

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

 22
PPG Coatings Europe BV, Oceanenweg 2, 1047 BB Amsterdam, The Netherlands Manufacturing plant: PPG Deco Polska sp. z.o.o. Lewkowiec Branch 63-400 Ostrow Wlkp, Lewkowiec 68, Poland 2812-CPR-GA5058 DoP951
ETA No 22/0790 - EAD 350402-00-1106, STEELGUARD™ 951 Reactive coating for fire protection of steel elements: Resistance to fire up to R180 Primer / topcoat compatibility: Passed exposure conditions Z ₂ , Z ₁ , Y, X See ETA for relevant characteristics



STEELGUARD™ 951

DECLARATION OF PERFORMANCE No. DOP 951/0

Signed for and on behalf of the manufacturer by:

Name: **Herman Putter**
 Function: **PC EMEA Marketing and Business Development Director**
 Place and date of issue: **Amsterdam, January 13, 2023**
 Signature: 

Signed for and on behalf of the manufacturer by:

Name: **Kees van Vliet**
 Function: **PMC Global R&D Manager Cellulosic PFP**
 Signature: **Amsterdam, January 13, 2023**


WARRANTY

PPG warrants (i) its title to the product, (ii) that the quality of the product conforms to PPG’s specifications for such product in effect at the time of manufacture and (iii) that the product shall be delivered free of the rightful claim of any third person for infringement of any U.S. patent covering the product. THESE ARE THE ONLY WARRANTIES THAT PPG MAKES AND ALL OTHER EXPRESS OR IMPLIED WARRANTIES, UNDER STATUTE OR ARISING

OTHERWISE IN LAW, FROM A COURSE OF DEALING OR USAGE OF TRADE, INCLUDING WITHOUT LIMITATION, ANY OTHER WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR USE, ARE DISCLAIMED BY PPG. Any claim under this warranty must be made by Buyer to PPG in writing within five (5) days of Buyer’s discovery of the claimed defect, but in no event later than the expiration of the applicable shelf life of the product, or one year from the date of the delivery of the product to the Buyer, whichever is earlier. Buyer’s failure to notify PPG of such non-conformance as required herein shall bar Buyer from recovery under this warranty.

LIMITATION OF LIABILITY

IN NO EVENT WILL PPG BE LIABLE UNDER ANY THEORY OF RECOVERY (WHETHER BASED ON NEGLIGENCE OF ANY KIND, STRICT LIABILITY OR TORT) FOR ANY INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES IN ANY WAY RELATED TO, ARISING FROM, OR RESULTING FROM ANY USE MADE OF THE PRODUCT. The information in this sheet is intended for guidance only and is based upon laboratory tests that PPG believes to be reliable. PPG may modify the information contained herein at any time as a result of practical experience and continuous product development. All recommendations or suggestions relating to the use of the PPG product, whether in technical documentation, or in response to a specific inquiry, or otherwise, are based on data, which to the best of PPG’s knowledge, is reliable. The product and related information is designed for users having the requisite knowledge and industrial skills in the industry and it is the end-user’s responsibility to determine the suitability of the product for its own particular use and it shall be deemed that Buyer has done so, as its sole discretion and risk. PPG has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Therefore, PPG does not accept any liability arising from any loss, injury or damage resulting from such use or the contents of this information (unless there are written agreements stating otherwise). Variations in the application environment, changes in procedures of use, or extrapolation of data may cause unsatisfactory results. This sheet supersedes all previous versions and it is the Buyer’s responsibility to ensure that this information is current prior to using the product. Current sheets for all PPG Protective & Marine Coatings Products are maintained at www.ppgpmc.com. The English text of this sheet shall prevail over any translation thereof.

The PPG logo is a registered trademark and all other trademarks herein are property of the PPG group of companies.

