

# KL5610/KL5610B

## Aqua-Kolor Resurfacer

### DESCRIPTION

Two-component, water based Cementitious Acrylic Latex

### PRINCIPAL CHARACTERISTICS

- Use in conjunction with other resurfacers and topcoats to provide a smooth decontaminable surface.
- Use for patching holes in poured concrete walls and floors.
- Use to level the porosity or roughness of concrete surfaces.

Note: Not recommended for Chemical Environments, if left untopcoated

### COLOR AND GLOSS LEVEL

- Gray
- Flat

### BASIC DATA AT 77°F (25°C)

Data for mixed product	
Number of components	Two
Mass density	16.3 lb/US gal (2.0 kg/l)
Volume solids	69 ± 3%
VOC (Supplied)	max. 0.0 lb/US gal (approx. 0 g/l)
Temperature resistance	To 250°F 121°C)
Dry to touch	1 hour
Dry to overcoat	12 hours
Dry to handle	6 hours
Shelf life	At least 60 months when stored cool and dry

#### Notes:

- Temperature resistance is maximum for DRY heat
- Dry Film per coat: Enough to patch holes up to 1" deep.
- Drying times listed may vary depending on temperature, humidity and air movement

### RECOMMENDED SUBSTRATE CONDITIONS AND TEMPERATURES

- The service life of the coating is directly related to the surface preparation.
- The surface to be coated must be properly prepared, dry, clean and free of contamination.

# KL5610/KL5610B

## Aqua-Kolor Resurfacer

### **Substrate temperature**

- DONOTUSE Above 120°F (49°C) and below 55°F (13°C), and at least 5°F (3°C) above dew point during application and curing

---

### **Warning**

Removal of old paint by sanding, scraping or other means may generate dust or fumes which contain lead. EXPOSURE TO LEAD DUST OR FUMES MAY CAUSE ADVERSE HEALTH EFFECTS, ESPECIALLY IN CHILDREN OR PREGNANT WOMEN. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted and approved (e.g., NIOSHapproved) respirator and proper containment and cleanup. For additional information, contact the USEPA/Lead Information Hotline at 1-800-424-LEAD or the regional Health Canada office

---

### **SYSTEM SPECIFICATION**

- Recommended basecoats: Hydro-Poxy Primer/Sealer.
- Recommended Topcoats: Aqua-Kolor Enamel, Aqua-Kolor Primer, Hydro-Poxy Wall Resurfacer and Hydro-Poxy Primer.

---

### **Pot life**

1 hour at 77°F (25°C)

---

### **Application**

- Squeegee or Broad Knife.
- Mix Ratio: Mix one two gallon containers of KL5610B with one gallon container of KL5610
- Mechanically agitate KL5610 prior to blending. Add KL5610B to Part A under agitation
- Thoroughly mix until uniform

Note: A squeegee or broad knife is recommended to smooth out the initial application of KL5610/KL5610B resurfacer and fill all holes, voids and other surface imperfections.

### **Material temperature**

Material temperature during application should be between 55°F (13°C) and 90°F (32°C)

---

### **Cleaning solvent**

Clean equipment with warm soapy water. Rinse with paint thinner to prevent rusting.

Note: Application equipment should be thoroughly cleaned at least every eight hours or each working shift.

### **ADDITIONAL DATA**

**Solvent and water-based paints should be stored indoors at a temperature range of 45-90 degrees F.**

- Water based paints should be kept from freezing.



# KL5610/KL5610B

## Aqua-Kolor Resurfacer

### SAFETY PRECAUTIONS

- Read all label and Safety Data Sheet (SDS) information prior to use.
- Not intended for residential use.

---

### WARRANTY

PPG warrants (i) its title to the product, (ii) that the quality of the product conforms to PPG's specifications for such product in effect at the time of manufacture and (iii) that the product shall be delivered free of the rightful claim of any third person for infringement of any U.S. patent covering the product. THESE ARE THE ONLY WARRANTIES THAT PPG MAKES AND ALL OTHER EXPRESS OR IMPLIED WARRANTIES, UNDER STATUTE OR ARISING OTHERWISE IN LAW, FROM A COURSE OF DEALING OR USAGE OF TRADE, INCLUDING WITHOUT LIMITATION, ANY OTHER WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR USE, ARE DISCLAIMED BY PPG. Any claim under this warranty must be made by Buyer to PPG in writing within five (5) days of Buyer's discovery of the claimed defect, but in no event later than the expiration of the applicable shelf life of the product, or one year from the date of the delivery of the product to the Buyer, whichever is earlier. Buyer's failure to notify PPG of such non-conformance as required herein shall bar Buyer from recovery under this warranty.

---

### AVAILABILITY

#### Packaging

3-gallon and 5-gallon kits.

1-gallon and 5-gallon kits

The PPG logo, and all other PPG marks are property of the PPG group of companies. All other third-party marks are property of their respective owners.

