

GORI 11

Wood Preservative



GORI 11 Wood Preservative is a water based wood coating that penetrates deep into the wood and offers extreme protection against blue stain, fungi, mould, insects and termites. Suitable for use on new or old wood and is compatible with both solvent and water based wood finishes.

GORI 11 Wood Preservative is not available in the Republic of Ireland.

KEY PROPERTIES

- ▶ **Protection for outdoor softwood against blue stain, mould, fungi, insects and termites**
- ▶ **Compatible with all wood finishes**
- ▶ **Penetrates deep into the wood**

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. To obtain maximum performance from this product, old paint and varnish should be completely removed. Treat fungal or algal growth with a Sterilisation Wash as directed. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during preparations of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information on our products and service please call 01924 354354.

APPLICATION

Ensure good ventilation during application and drying. Easy to apply by brush or roller. Stir well.

Do not apply when moisture of the wood is above 18% at the time of treatment or if the temperature is below +5°C and relative humidity is below 80%. Avoid application in damp conditions or externally when rain is imminent.

Apply one coat at a rate of 500ml per 2.5 square metres with a brush or roller. Do not thin.

COVERAGE

GORI 11 Wood Preservative will cover approximately 5 m²/l.

DRYING TIME

Touch dry: 1 hour. Apply top coat after: app 12 hours (measured at 23°C and standard humidity of 60%).

CLEANER

Clean Water

COLOUR RANGE

Available in Clear

SIZE

Available in 2.5L & 5L

AFTER USE

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use in soapy water and rinse thoroughly. Do not empty product into drains or water courses. Some local authorities have special facilities for the disposal of waste coatings.

STORAGE

SHELF LIFE: 2 YEARS

Keep container tightly closed. To avoid the risk of spillage, always store and transport in a secure upright position. As wood is an organic material, there is no guarantee that the same wood species will react the same way in different areas, when treated/coated/stained. Lift with care – gross weight does not exceed 8 kilograms.

EU limit value for this product (Cat A/h): 30 g/l (2010).

This product contains max 15g/l VOC

SAFE USE INFORMATION

Keep out of reach of children.

Avoid contact with skin and eyes.

Do not ingest.

Do not breathe spray. Wear respiratory protection.

If medical advice is needed have container or label to hand.

Please refer to Product label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency.

SDS available by calling 01924 354 354.

